Relation of the wave–propagation metric tensor to the curvatures of the slowness and ray–velocity surfaces

Luděk Klimeš

Department of Geophysics, Charles University, Ke Karlovu 3, 121 16 Praha 2, Czech Republic, Fax: +420-2-2191 1214, E-mail: klimes@seis.karlov.mff.cuni.cz

Summary

The contravariant components of the wave–propagation metric tensor equal half the second–order partial derivatives of the selected eigenvalue of the Christoffel matrix with respect to the slowness–vector components. The relations of the wave–propagation metric tensor to the curvature matrix and Gaussian curvature of the slowness surface and to the curvature matrix and Gaussian curvature of the ray–velocity surface are demonstrated with the help of ray–centred coordinates.

Keywords

Ray theory, seismic anisotropy, Finsler space, metric tensor, slowness surface, ray–velocity surface, ray–centred coordinates.

1. Introduction

Rays corresponding to the ray theory for anisotropic media represent geodesics in Finsler space with the Finslerian metric determined by the *wave–propagation metric tensor* (Rund 1959; Babich 1961; Hanyga 1984; Červený 2002). The contravariant components of the wave–propagation metric tensor equal half the second–order partial derivatives of the selected eigenvalue of the Christoffel matrix with respect to the slowness–vector components. The covariant wave–propagation metric tensor is the matrix inverse to the contravariant wave–propagation metric tensor.

The contravariant components of the wave–propagation metric tensor are closely related to the curvature matrix of the slowness surface. The covariant components of the wave–propagation metric tensor are closely related to the curvature matrix of the ray–velocity surface. We shall demonstrate these relations by transforming the contravariant and covariant wave–propagation metric tensors into ray–centred coordinates.

In this paper, lower–case Roman indices take values $i, j, ... = 1, 2, 3$, upper–case Roman indices take values $I, J, ... = 1, 2$, and the Einstein summation convention applies to pairs of identical indices.

In: Seismic Waves in Complex 3-D Structures, Report 12 (Department of Geophysics, Charles University, Prague, 2002), pp. 79–87; to appear in *Studia Geophysica et Geodaetica*, **46** (2002), No. 3

2. Finslerian wave–propagation metric tensor

Let $G(x^m, p_n)$ be a selected eigenvalue of the Christoffel matrix

$$\Gamma_{jk}(x^m, p_n) = p_i \, a_{ijkl}(x^m) \, p_l \quad . \tag{1}$$

Here x^m are Cartesian coordinates, $a_{ijkl}(x_m)$ are density–normalized elastic moduli, and p_i are the components of the slowness vector, defined as partial derivatives of travel time (action) τ,

$$p_i = \frac{\partial \tau}{\partial x^i} \quad . \tag{2}$$

Refer, e.g., to the book by Červený (2001) for a more detailed description.

All geometrical objects considered in this paper, such as the sheets of the slowness surface, sheets of the ray–velocity surface or phase–space rays, satisfy equation

$$G(x^m, p_n) = 1 \quad . \tag{3}$$

The *ray–velocity vector* (group–velocity vector) $V^i(x^m, p_n)$ is defined by equation

$$V^i = \frac{1}{2} \frac{\partial G}{\partial p_i} \quad . \tag{4}$$

The *contravariant wave–propagation metric tensor* is defined by equation

$$G^{ij}_{(x)} = \frac{1}{2} \frac{\partial^2 G}{\partial p_i \partial p_j} \tag{5}$$

(Rund 1959, eq. 1.5.4; Hanyga 1984, eq. 2.3.76; Asanov 1985, eq. 6.20; Klimeš 1994, sec. 6; Červený 2002, eq. 54). This contravariant tensor is also used in the dynamic ray tracing equations for anisotropic media (Červený 1972, eq. 32). Tensor (5) may also be expressed as the partial derivative of the ray–velocity vector (4),

$$G^{ij}_{(x)} = \frac{\partial V^i}{\partial p_j} \quad . \tag{6}$$

Eigenvalues $G(x^m, p_n)$ of the Christoffel matrix are homogeneous functions of the second degree with respect to p_i, which is the direct consequence of equation (1) and of the definition of eigenvalues. Euler's theorem on homogeneous functions then yields $V^i p_i = G$ and

$$G^{ij}_{(x)} \, p_j = V^i \quad . \tag{7}$$

Relation $V^i p_i = G$ reads

$$V^i p_i = 1 \tag{8}$$

on all geometrical objects which satisfy equation (3).

The *covariant wave–propagation metric tensor* $G^{(x)}_{ij}$ is the inverse matrix to the contravariant wave–propagation metric tensor,

$$G^{(x)}_{ij} G^{jk}_{(x)} = \delta^k_i \tag{9}$$

(Rund 1959, eq. 1.5.9). Equation (7) then yields

$$p_i = G^{(x)}_{ij} V^j \quad . \tag{10}$$

Anisotropic ray theory rays are the geodesics in Finsler space with the Finslerian metric determined by the wave–propagation metric tensor. Refer, e.g., to the books by Rund (1959) or Asanov (1985) for the Finsler geometry.

Mapping $V^i = V^i(x^m, p_n)$ defined by equation (4) may not be uniquely invertible with respect to p_i. Inverse mapping $p_i = p_i(x^m, V^n)$ can thus be defined only locally, in the vicinity of a chosen ray–velocity vector V^l. Inverting equation (6), we may express the covariant wave–propagation metric tensor locally as the partial derivative of slowness vector $p_i = p_i(x^m, V^n)$ with respect to the components of the ray–velocity vector,

$$G_{ij}^{(x)} = \frac{\partial p_i}{\partial V^j} \quad . \tag{11}$$

The local expression

$$\frac{1}{2}\frac{\partial G}{\partial V^i} = V^j G_{ji}^{(x)} = p_i \tag{12}$$

for the first derivatives of $G(x^m, p_n(x^k, V^l))$ with respect to V^i follows from equations (4), (10) and (11). The local expression

$$\frac{1}{2}\frac{\partial^2 G}{\partial V^i \partial V^j} = \frac{\partial p_i}{\partial V^j} = G_{ij}^{(x)} \tag{13}$$

(Rund 1959, eq. 1.3.1) for the second derivatives of $G(x^m, p_n(x^k, V^l))$ with respect to V^i follows from equations (11) and (12).

3. Ray–centred coordinates for anisotropic media

The q^3–coordinate line of ray–centred coordinates q^m is a selected ray, parametrized by travel time $q^3 = \tau$. Coordinates q^1 and q^2 lie, for fixed q^3, in the plane tangent to the wavefront (Hanyga 1982; Kendall, Guest & Thomson 1992; Klimeš 1994). The Cartesian coordinates corresponding to q^m are

$$x^i = x_0^i(q^3) + h_M^i(q^3)\ q^M \quad , \tag{14}$$

where $x_0^i(\tau)$ are points of the selected ray. Relation (14) is both the definition of the ray–centred coordinates, and the transformation equation from ray–centred to Cartesian coordinates. Basis vectors $h_M^i(\tau)$ are chosen arbitrarily in the plane tangent to the wavefront,

$$p_i\, h_M^i = 0 \quad . \tag{15}$$

The transformation matrices, taken at the central ray, are

$$h_m^i = \frac{\partial x^i}{\partial q^m} \quad , \tag{16}$$

and

$$\hat{h}_i^m = \frac{\partial q^m}{\partial x^i} \quad , \tag{17}$$

where "contravariant basis vectors" h_1^i, h_2^i, h_3^i of the ray–centred coordinate system and "covariant basis vectors" $\hat{h}_i^1$, $\hat{h}_i^2$, $\hat{h}_i^3$ of the ray–centred coordinate system are mutually biorthonormal, i.e. satisfy relations

$$h_m^i\, \hat{h}_j^m = \delta_j^i \quad , \qquad \hat{h}_i^m\, h_n^i = \delta_n^m \quad . \tag{18}$$

Vector h_3^i is tangent to the ray,

$$h_3^i = V^i \quad , \tag{19}$$

which follows from the ray tracing equations (Červený 1972, eq. 13). Vector $\hat{h}_i^3$ is normal to the wavefront,

$$\hat{h}_i^3 = p_i \quad , \tag{20}$$

see (2). Vectors $\hat{h}_i^1$ and $\hat{h}_i^2$ are normal to the ray,

$$V^i \, \hat{h}_i^M = 0 \quad , \tag{21}$$

as follows from (18) and (19). Equations (18), (19) and (20) can serve as the definition of transformation matrices h_m^i and $\hat{h}_i^m$. The ray–centred coordinates for anisotropic media may or may not converge to the ray–centred coordinates (Riemannian normal coordinates) for isotropic media used by Luneburg (1944), Babich & Buldyrev (1972) or Popov & Pšenčík (1978a; 1978b). The isotropic limit depends on additional constraints imposed on vectors h_1^i and h_2^i (Klimeš 1994).

Vectors h_1^i and h_2^i need not be orthonormal. The non–orthonormality of vectors h_1^i and h_2^i may be quantified by positive–definite symmetric 2×2 matrix

$$h_{MN} = h_M^i \, h_N^i \quad . \tag{22}$$

Analogously, the non–orthonormality of vectors $\hat{h}_i^1$ and $\hat{h}_i^2$ may be quantified by positive–definite symmetric 2×2 matrix

$$\hat{h}^{MN} = \hat{h}_i^M \, \hat{h}_i^N \quad . \tag{23}$$

Vectors h_1^i and h_2^i would be orthonormal if $h_{MN} = \delta_{MN}$, whereas vectors $\hat{h}_1^i$ and $\hat{h}_2^i$ would be orthonormal if $\hat{h}^{MN} = \delta^{MN}$. Equations (8), (15), (19) and (22) yield

$$\det\bigl(h_m^i\bigr) = \epsilon_{ijk} \, h_1^i h_2^j h_3^k = \pm\sqrt{\det\bigl(h_{MN}\bigr)} \; v p_k V^k = \pm v \sqrt{\det\bigl(h_{MN}\bigr)} \quad , \tag{24}$$

where

$$v = (p_i p_i)^{-\frac{1}{2}} \tag{25}$$

is the *phase velocity*. Equations (8), (20), (21) and (23) yield

$$\det\bigl(\hat{h}_i^m\bigr) = \epsilon^{ijk} \, \hat{h}_i^1 \hat{h}_j^2 \hat{h}_k^3 = \pm\sqrt{\det\bigl(\hat{h}^{MN}\bigr)} \; V^{-1} V^k p_k = \pm V^{-1} \sqrt{\det\bigl(\hat{h}^{MN}\bigr)} \quad , \tag{26}$$

where

$$V = \sqrt{V^i V^i} \tag{27}$$

is the *ray velocity* (group velocity). Equations (18), (24) and (26) yield

$$\det\bigl(h_{MN}\bigr) \, \det\bigl(\hat{h}^{KL}\bigr) = \left(\frac{V}{v}\right)^2 \quad . \tag{28}$$

Note that if we choose vectors h_1^i and h_2^i orthonormal, $h_{MN} = \delta_{MN}$, we cannot choose vectors $\hat{h}_i^1$ and $\hat{h}_i^2$ orthonormal, and vice versa.

The contravariant wave–propagation metric tensor transformed into ray–centred coordinates,

$$G_{(q)}^{mn} = G_{(x)}^{ij} \, \hat{h}_i^m \, \hat{h}_j^n \quad , \tag{29}$$

is used in the dynamic ray tracing equations in ray–centred coordinates. Equations (7), (8), (20) and (21) yield

$$G_{(q)}^{M3} = G_{(q)}^{3M} = 0 \tag{30}$$

and

$$G^{33}_{(q)} = 1 \tag{31}$$

(Klimeš 1994, eqs. 49e, 49f). The 2×2 submatrix $G^{MN}_{(q)}$ depends on the choice of vectors h^i_1 and h^i_2 in the plane tangent to the wavefront. Due to equations (30) and (31), the determinant of the 2×2 submatrix $G^{MN}_{(q)}$ equals the determinant of the 3×3 matrix $G^{MN}_{(q)}$,

$$\det\bigl(G^{MN}_{(q)}\bigr) = \det\bigl(G^{mn}_{(q)}\bigr) \quad . \tag{32}$$

Equations (26) and (29) yield

$$\det\bigl(G^{mn}_{(q)}\bigr) = V^{-2}\,\det\bigl(\hat{h}^{MN}\bigr)\,\det\bigl(G^{ij}_{(x)}\bigr) \quad . \tag{33}$$

The covariant wave–propagation metric tensor transformed into ray–centred coordinates is

$$G^{(q)}_{mn} = G^{(x)}_{ij}\,h^i_m\,h^j_n \quad . \tag{34}$$

Unlike contravariant wave–propagation metric tensor $G^{mn}_{(q)}$, covariant wave–propagation metric tensor $G^{(q)}_{mn}$ in ray–centred coordinates has found no significant application yet. Equations (8), (10), (15) and (19) yield

$$G^{(q)}_{M3} = G^{(q)}_{3M} = 0 \tag{35}$$

and

$$G^{(q)}_{33} = 1 \quad . \tag{36}$$

Identities (35) and (36) may also be obtained by inverting matrix $G^{mn}_{(q)}$ which satisfies (30) and (31). Due to equations (35) and (36), the determinant of 2×2 submatrix $G^{(q)}_{MN}$ equals the determinant of 3×3 matrix $G^{(q)}_{mn}$,

$$\det\bigl(G^{(q)}_{MN}\bigr) = \det\bigl(G^{(q)}_{mn}\bigr) \quad . \tag{37}$$

Equations (24) and (34) yield

$$\det\bigl(G^{(q)}_{mn}\bigr) = v^2\,\det\bigl(h_{MN}\bigr)\,\det\bigl(G^{(x)}_{ij}\bigr) \quad . \tag{38}$$

4. Curvature of the slowness surface

The *slowness surface* (phase–slowness surface, index surface) at spatial point x^m is composed of three sheets corresponding to the three eigenvalues of the Christoffel matrix. The sheet, corresponding to a selected eigenvalue G of the Christoffel matrix, is the set of slowness vectors p_i satisfying equation (3). Each of the three sheets of the slowness surface may be parametrized by unit vector vp_i.

Curvature matrix K^{MN} of the slowness surface is defined with respect to two orthonormal vectors $\hat{e}^1_i$ and $\hat{e}^2_i$,

$$\hat{e}^M_i\,\hat{e}^N_i = \delta^{MN} \quad , \tag{39}$$

tangent to the slowness surface and thus perpendicular to the ray–velocity vector V^i,

$$\hat{e}^M_i\,V^i = 0 \quad . \tag{40}$$

The curvature matrix of the slowness surface is determined by the second derivatives of G, expressed with respect to orthonormal vectors $\hat{e}^M_i$, divided by the norm of the gradient of G, see (4), (5) and (27),

$$K^{MN} = V^{-1}\,\hat{e}^M_i\,G^{ij}_{(x)}\,\hat{e}^N_j \quad . \tag{41}$$

The orthonormal vectors may be chosen as

$$\hat{e}_i^M = \hat{h}_i^N \, [\hat{h}^{-\frac{1}{2}}]^{NM} \quad , \tag{42}$$

where $[\hat{h}^{-\frac{1}{2}}]^{MN}$ stands for the components of the $-\frac{1}{2}$th power of 2×2 matrix $\hat{h}^{MN}$. Note that the functions of symmetric matrices may conveniently be defined in terms of the eigenvectors and the functions of the eigenvalues. For option (42), equations (29) and (41) yield

$$K^{MN} = V^{-1} [\hat{h}^{-\frac{1}{2}}]^{MK} \, G_{(q)}^{KL} \, [\hat{h}^{-\frac{1}{2}}]^{LN} \quad . \tag{43}$$

Note that equation (43) would simplify to $K^{MN} = V^{-1} G_{(q)}^{MN}$ if vectors $\hat{h}_i^1$ and $\hat{h}_i^2$ were chosen orthonormal.

The *Gaussian curvature of the slowness surface* (total curvature of the slowness surface) is then

$$\det\big(K^{MN}\big) = \frac{\det\big(G_{(q)}^{MN}\big)}{V^2 \det\big(\hat{h}^{KL}\big)} \quad . \tag{44}$$

Equations (32), (33) and (44) yield the Gaussian curvature of the slowness surface in the form

$$\boxed{\det\big(K^{MN}\big) = V^{-4} \det\big(G_{(x)}^{ij}\big) \quad .} \tag{45}$$

Equations (27), (39) and (40) yield

$$\hat{e}_i^M \, \hat{e}_j^M = \delta_{ij} - V^{-2} V^i V^j \quad . \tag{46}$$

Inserting (46) into (41), we obtain expression

$$\boxed{\tfrac{1}{2} K^{MM} = \tfrac{1}{2} \big(V^{-1} G_{(x)}^{ii} - V^{-3} V^i G_{(x)}^{ij} V^j\big)} \tag{47}$$

for the *mean curvature of the slowness surface*. Equations (45) and (47) may also be used to calculate eigenvalues

$$\tfrac{1}{2} K^{MM} \pm \sqrt{\big(\tfrac{1}{2} K^{MM}\big)^2 - \det\big(K^{MN}\big)} \tag{48}$$

of the curvature matrix K^{MN} of the slowness surface (*principal normal curvatures of the slowness surface*).

5. Curvature of the ray–velocity surface

The *ray–velocity surface* (group–velocity surface, Fresnel wave surface) at spatial point x^m is composed of three sheets corresponding to the three eigenvalues of the Christoffel matrix. The sheets of the ray–velocity surface are images of the corresponding sheets of the slowness surface with mapping

$$V^i = V^i(x^m, p_n) \tag{49}$$

defined by equation (4). Each sheet of the ray–velocity surface at spatial point x^m is thus a set of ray–velocity vectors (49), where slowness vector p_i satisfies equation (3). Each of the three sheets of the ray–velocity surface may be parametrized by unit vector vp_i, analogously to the sheets of the slowness surface, but cannot be uniquely parametrized by unit vector $V^{-1}V^i$.

The normal to the ray–velocity surface is given by slowness vector p_i, see (12). *Curvature matrix K_{MN} of the ray–velocity surface* is defined with respect to two orthonormal vectors e_1^i and e_2^i,

$$e_M^i\, e_N^i = \delta_{MN} \quad , \tag{50}$$

tangent to the ray–velocity surface and thus perpendicular to slowness vector p_i,

$$e_M^i\, p_i = 0 \quad . \tag{51}$$

The curvature matrix of the ray–velocity surface is determined by the second derivatives of $G(x^m, p_n(V^k))$ with respect to V^k, transformed into orthonormal vectors e_M^i, and divided by the norm of the gradient of G with respect to V^k,

$$K_{MN} = v\; e_M^i\, G_{ij}^{(x)}\, e_N^j \quad , \tag{52}$$

see (12), (13) and (25). The orthonormal vectors may be chosen as

$$e_M^i = h_N^i\, [h^{-\frac{1}{2}}]_{NM} \quad , \tag{53}$$

where $[h^{-\frac{1}{2}}]_{MN}$ stands for the components of the $-\frac{1}{2}$th power of $2{\times}2$ matrix h_{MN}. For option (53), equations (34) and (52) yield

$$K_{MN} = v\; [h^{-\frac{1}{2}}]_{MK}\, G_{KL}^{(q)}\, [h^{-\frac{1}{2}}]_{LN} \quad . \tag{54}$$

Note that equation (54) would simplify to $K_{MN} = v\, G_{MN}^{(q)}$ if vectors h_1^i and h_2^i were chosen orthonormal.

The *Gaussian curvature of the ray–velocity surface* (total curvature of the ray–velocity surface) is then

$$\det\big(K^{MN}\big) = \frac{v^2\, \det\big(G_{KL}^{(q)}\big)}{\det\big(h_{MN}\big)} \quad . \tag{55}$$

Equations (37), (38) and (55) yield the Gaussian curvature of the ray–velocity surface in the form

$$\boxed{\det\big(K_{MN}\big) = v^4\, \det\big(G_{ij}^{(x)}\big) \quad .} \tag{56}$$

Equations (25), (50) and (51) yield

$$e_M^i\, e_M^j = \delta^{ij} - v^2 p_i p_j \quad . \tag{57}$$

Inserting (57) into (52), we obtain expression

$$\tfrac{1}{2}K_{MM} = \tfrac{1}{2}\big(v\, G^{(x)}_{ii} - v^3 p_i\, G^{(x)}_{ij} p_j\big) \tag{58}$$

for the *mean curvature of the ray–velocity surface*. Equations (56) and (58) may also be used to calculate eigenvalues

$$\tfrac{1}{2}K_{MM} \pm \sqrt{(\tfrac{1}{2}K_{MM})^2 - \det\big(K_{MN}\big)} \tag{59}$$

of the curvature matrix K_{MN} of the ray–velocity surface (*principal normal curvatures of the ray–velocity surface*).

The product of equations (45) and (56) yields relation

$$\det\big(K^{MN}\big)\, \det\big(K_{KL}\big) = \Big(\frac{v}{V}\Big)^4 \tag{60}$$

derived by Grechka & Obolentseva (1993, eq. 17) and Vavryčuk & Yomogida (1996, eq. B.6).

Acknowledgements

I am greatly indebted to Vlastislav Červený who introduced me to elastic wave propagation and the ray theory in particular.

Vlastislav Červený directed my attention to Finsler geometry, and Václav Vavryčuk formulated the problem studied in this paper. The comments and suggestions of Ivan Pšenčík and Václav Vavryčuk enabled the improvement of this paper.

This research has been supported by the Grant Agency of the Czech Republic within Grant Projects 205/01/0927 and 205/01/D097, by the Grant Agency of the Charles University under Contracts 237/2001/B-GEO/MFF and 229/2002/B-GEO/MFF, by the Ministry of Education of the Czech Republic within Research Project J13/98-113200004, and by the members of the consortium "Seismic Waves in Complex 3-D Structures" (see "http://sw3d.mff.cuni.cz").

References

Asanov, G.S. (1985): Finsler Geometry, Relativity and Gauge Theories. D. Reidel Publ. Co., Dordrecht.

Babich, V.M. (1961): Ray method of calculating the intensity of wavefronts in the case of a heterogeneous, anisotropic, elastic medium (in Russian). In: Problems of the Dynamic Theory of Propagation of Seismic Waves, Vol. V, pp. 36–46. English translation: *Geophys. J. int.*, **118**(1994), 379–383.

Babich, V.M. & Buldyrev, N.J. (1972): Asymptotic Methods in Problems of Diffraction of Short Waves (in Russian). Nauka, Moscow.

Červený, V. (1972): Seismic rays and ray intensities in inhomogeneous anisotropic media. *Geophys. J. R. astr. Soc.*, **29**, 1–13.

Červený, V. (2001): Seismic Ray Theory. Cambridge Univ. Press, New York.

Červený, V. (2002): Fermat's variational principle for anisotropic inhomogeneous media. *Stud. geophys. geod.*, **46**, No. 3.

Grechka, V.Yu. & Obolentseva, I.R. (1993): Geometrical structure of shear wave surfaces near singularity directions in anisotropic media. *Geophys. J. int.*, **115**, 609–616.

Hanyga, A. (1982): Dynamic ray tracing in an anisotropic medium. *Tectonophysics*, **90**, 243–251.

Hanyga, A. (ed.) (1984): Seismic Wave Propagation in the Earth. PWN (Elsevier), Warszawa (Amsterdam).

Kendall, J-M., Guest, W.S. & Thomson, C.J. (1992): Ray–theory Green's function reciprocity and ray–centred coordinates in anisotropic media. *Geophys. J. int.*, **108**, 364–371.

Klimeš, L. (1994): Transformations for dynamic ray tracing in anisotropic media. *Wave Motion*, **20**, 261–272.

Luneburg, R.K. (1944): Mathematical Theory of Optics. Lecture notes, Brown University, Providence, Rhode Island. Reedition: University of California Press, Berkeley and Los Angeles, 1964.

Popov, M.M. & Pšenčík, I. (1978a): Ray amplitudes in inhomogeneous media with curved interfaces. *Travaux Instit. Géophys. Acad. Tchécosl. Sci. No. 454, Geofys. Sborník*, **24**, 111–129, Academia, Praha.

Popov, M.M. & Pšenčík, I. (1978b): Computation of ray amplitudes in inhomogeneous media with curved interfaces. *Stud. geophys. geod.*, **22**, 248–258.

Rund, H. (1959): The Differential Geometry of Finsler Spaces. Springer, Berlin–Göttingen–Heilderberg.

Vavryčuk, V. & Yomogida, K. (1996): SH–wave Green tensor for homogeneous transversely isotropic media by higher–order approximations in asymptotic ray theory. *Wave Motion*, **23**, 83–93.